

Rx36

- 3-way compact versatile full range system
- Light weight, very high power of 900W
- Unique 2" coaxial neodymium driver
- Neodymium 15" ultra low distortion woofer
- Passive or Bi-amplified operation
- Designed for fixed installation and touring


Applications:

Theatre, Corporate Events, Club, Stage monitor, Band PA




The Coda Audio Rx36 is a versatile, full range, three-way loudspeaker system that features a high power 15" neodymium woofer and a 2" coaxial neodymium driver coupled to a 60° x 40° waveguide. As a 3-way system, the Rx36 may be driven passively or with bi-amplification to provide extremely high acoustic output.

The Rx36 incorporates a multidesign enclosure fitted with two M6 threaded points for use with an optional U-bracket and includes an integral top hat. Integrated air cargo flying tracks enable easy suspension for both fixed installations using M6 eyebolts or touring applications using clip-on cargo spring stud.



U-bracket
vertical



U-bracket



24481
Wall mount



68620
Truss clamp

TECHNICAL SPECIFICATIONS:

■	3-way full range multi design
Application:	High level short/medium throw or stage monitor
Frequency response:	50 Hz - 21k Hz (- 3 dB)
Power handling AES:	900 W
Peak power:	3600 W
Sensitivity:	99 dB
Max. SPL peak:	133 dB
Dispersion:	60° x 40°
Components:	
■	15" neodymium woofer
	4" (101.6 mm) voice coil, 900 W (AES)
High frequency:	2" neodymium coaxial driver
	3.5" (90 mm) + 1.75" (44.4 mm) VC,
	150 W + 80 W
Crossover:	700 Hz, 6.3 kHz Passive
Nominal impedance:	8 Ohm
Input connectors:	2 x Neutrik™ NL4MP
Suspension Rx32M:	2x air cargo tracks
	8 x M6 treaded points
Enclosure material:	15 mm plywood
Finish:	textured black paint
Dimensions:	420 x 66 x 380 mm
Net weight:	25 kg